

**WELLS
CARGO®**

THE ALL NEW STEEL SPORTTRAC™



Trailers shown may feature optional equipment available at an additional charge.

The new Wells Cargo® steel SportTrac mid-deck is your no limits trailer for all your powersport toys. An all-steel frame offers plenty of strength and long-lasting durability. Ramp doors, front & rear, for quick takeoffs on arrival and easy loading when heading back home. The mid-deck platform height is a hybrid design with drive over wheel boxes. Perfect for all your off-road throttle machines.

SPORTTRAC™

SPECIFICATIONS

		STMS8522T2	STMS8522T3	STMS8528T3	STMS8530T3
Body:	Length	22'0"	22'0"	28'0"	30'0"
	Width	8'4"	8'4"	8'4"	8'4"
Overall:	Length	24'9"	24'9"	30'9"	32'9"
	Width	8'6"	8'6"	8'6"	8'6"
	Height	9'2"	9'2"	9'2"	9'2"
Interior:	Length (including "V")	21'8"	21'8"	27'8"	29'8"
	Width	8'1"	8'1"	8'1"	8'1"
	Height	7'0"	7'0"	7'0"	7'0"
Width Between Wheel Boxes		83"	83"	83"	83"
Platform Height		21"	21"	21"	21"
Torflex® Suspension E-Z® Lube Axles:	Qty Type	Tandem 45° Down	Tandem 45° Down	Tandem 45° Down	Tandem 45° Down
Electric Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size		ST205/75R15	ST225/75R15	ST225/75R15	ST225/75R15
Tire Load Range		C	D	D	D
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		23"	23"	23"	23"
Hitch Weight (% of Curb Weight)		10% to 15%	10% to 15%	10% to 15%	10% to 15%
GVWR		7,000 lb.	9,990 lb.	9,990 lb.	9,990 lb.
Curb Weight (Approximate)		3,320 lb.	3,420 lb.	4,230 lb.	4,530 lb.
Payload Capacity (Approximate)		3,680 lb.	6,570 lb.	5,760 lb.	5,460 lb.
Flush Lock Side Door Width - Width x Height		36" x 78"	36" x 78"	36" x 78"	36" x 78"
Front Ramp Door Opening - Width x Height		66" x 78"	66" x 78"	66" x 78"	66" x 78"
Rear Ramp Door Opening - Width x Height		94" x 83"	94" x 83"	94" x 83"	94" x 83"
Beavertail Length		48"	48"	48"	48"
12v Male Connection		7-way	7-way	7-way	7-way

STANDARD FEATURES

- 6' V-Front with Polished Aluminum Front Nose
- Mid-Deck Platform with Tapered Drive Over Wheel Boxes
- 94"W Rear Ramp Door with Spring Assist
- 48" Beavertail
- 66"W Front Ramp Door
- 36" Side Entry Door with Fold Down Steel Step (Road Side)
- 16" OC Floor Crossmembers
- 16" OC Tube Vertical Wall Posts
- 16" OC Tube Roof Framing
- 2000 lb. Front Wind Tongue Jack
- 3-Piece A-Frame
- Smooth Aluminum Fenderettes
- Torflex® Torsion Axles
- Radial Tires with Aluminum Wheels
- 3/4" PlexCore™ High-Performance Flooring
- White Vinyl Interior Sidewall Liner
- ATP Kickplate (12"H)
- 12v LED Interior Dome Lights (2) with Switch
- 12v LED Exterior Lighting Tail/Clearance Lights
- LED Rear ID Bar with Loading Light with Switch
- 1-Piece Aluminum Roof
- Bonded .030 Aluminum Exterior (Smooth Appearance)
- Flow-Thru Sidewall Vents
- 14in x 14in Non-Powered Roof Vent
- 5,000 lb. D-Rings (6)
- 24" ATP Stoneguard
- 14" x 14" Access/Fuel Door
- 3-Year Limited Warranty



Trailers shown may feature optional equipment available at additional cost.