

The Wells Cargo logo is a black circle with the words "WELLS" and "CARGO" stacked vertically in white, bold, sans-serif capital letters. The background of the entire advertisement is a photograph of a person in safety gear (orange jacket, orange helmet with a clear face shield, and yellow gloves) leaning over a black metal trailer. The person is using a chainsaw to cut a large log. The trailer is a single-axle, enclosed cargo trailer with a side door and a hitch at the front. The scene is set outdoors, likely at a logging site, with a blurred background of trees and a bright sky.

**WELLS
CARGO®**

FASTTRAC® 8.5' WIDE THE ALL PURPOSE TRAILER

VALUE-DRIVEN WITH A SPIRIT THAT'S BORN TO HAUL!

The FastTrac® brings a whole new level of value to the light-duty recreational cargo trailer market. A balanced combination of versatility and affordability, the FastTrac® delivers on all fronts. From its unpretentious styling to its uncompromising dependability, only Wells Cargo® could pack so much value into an entry-level trailer.

Trailer shown features Deluxe Package available at an additional charge.

FASTTRAC®

SPECIFICATIONS



	FT85162	FT85202	FT85242
Body: Length Width	17' 6" 8' 4"	21' 6" 8' 4"	25' 6" 8' 4"
Overall: Length Width Height	19' 8" 8' 6" 8' 2"	23' 8" 8' 6" 8' 2"	27' 8" 8' 6" 8' 2"
Interior: Length Width Height	17' 3" 8' 1" 6' 6"	21' 3" 8' 1" 6' 6"	25' 3" 8' 1" 6' 6"
Width Between Wheel Wells	83"	83"	83"
Platform Height	19"	19"	19"
Spring Suspension E-Z Lube® Axles: Qty Total Axle Capacity	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
Electric Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	18"	18"	18"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)	2,670 lbs.	3,060 lbs.	3,280 lbs.
GVWR	7,000 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approximate)	4,330 lbs.	3,940 lbs.	3,720 lbs.
Rear Ramp Door Opening - Width x Height	94" x 72"	94" x 72"	94" x 72"
Side Door Opening - Width x Height	32" x 72"	32" x 72"	32" x 72"
12v Trailer End Connector	7-way	7-way	7-way
Tube Main Rails	2" x 6"	2" x 6"	2" x 6"

STANDARD FEATURES

- Exclusive Bull Nose Profile
- 15" Radial Tires with Silver Mod Wheels
- Smooth Aluminum Radius Fenderettes
- White .024 Aluminum Exterior *(With Screws)*
- 1-Piece Aluminum Roof
- 12v LED Exterior Lighting
- 12v LED Slim Line Tail Lights
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist & 16" Ramp Extension
- 32" Side Door with Bar Lock
- 12v Dome Light with Self-Switch
- Economy Sidewall Liner
- 3/4" High Performance PlexCore™ Decking
- 500 lb. Surface Wall Mounted Rope Rings (4)
- Spring Axles with 4" Drop
- E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit
- Undercoated Chassis
- 16" OC Vertical Posts
- 24" OC Crossmembers
- 24" OC Tube Roof Bows
- 1-Year Limited Warranty

DELUXE PACKAGE UPGRADES

- .030 Aluminum Exterior
- Exterior Color Options
- 3/8" PlexCore™ Sidewall Liner
- 5,000 lb. Floor D-Rings (4)



Trailers shown features Deluxe Package available at additional charge.



Standard Interior Shown with Economy Wall Liner & 500 lb. Rope Rings



www.wellscargo.com

Wells Cargo reserves the right to change or alter any specification, feature, option, package and/or pricing **without** notice. Some trailers are shown with optional equipment available at additional charge. See your authorized Wells Cargo dealer for more information.