



## **SPECIFICATIONS**



	FT58S2	FT610S2	FT612S2	FT714T2	FT716T2
Body: Length Width	9' 4" 5' 0"	11' 4" 6' 0"	13' 4" 6' 0"	15' 4" 7' 0"	17' 4" 7' 0"
Length Overall: Width Height	11' 4" 6' 8" 7' 1"	14' 0" 7' 8" 8' 1"	16' 0" 7' 8" 8' 1"	18' 0" 8' 6" 8' 2"	20' 0" 8' 6" 8' 2"
Length Interior: Width Height	9' 1" 4' 9" 5' 6"	11' 1" 5' 9" 6' 6"	13' 1" 5' 9" 6' 6"	15' 1" 6' 9" 6' 6"	17' 1" 6' 9" 6' 6"
Platform Height	17"	17"	17"	18"	18"
Spring Suspension E-Z Lube® Axles: Qty Total Axle Capacity	Single 3,500 lbs.	Single 3,500 lbs.	Single 3,500 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
Brakes with Breakaway Kit	N/A	Optional	Optional	4-Wheel Electric Drum	4-Wheel Electric Drum
Radial Tire Size Tire Load Range	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
Hitch Ball Size	2"	2"	2"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	16"	16"	16"	17"	17"
Hitch Weight (% of Curb Weight)	10% to 15%				
Curb Weight (Approximate)	965 lbs.	1,090 lbs.	1,225 lbs.	1,955 lbs.	2,115 lbs.
GVWR	2,990 lbs.	2,990 lbs.	2,990 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approximate)	2,065 lbs.	1,900 lbs.	1,765 lbs.	5,045 lbs.	4,8855 lbs.
Rear Door Opening - Width x Height	54" x 60"	66" x 72"	66" x 72"	78" x 72"	78" x 72"
Side Door Opening - Width x Height	N/A	32' x 72"	32' x 72"	32' x 72"	32' x 72"
12v Male Connection	4-way	4-way	4-way	7-way	7-way
Tube Main Rails	2" x 3"	2" x 3"	2" x 3"	2" x 4"	2" x 4"

## STANDARD FEATURES

- V-Front/Flat Roof Profile
- 15" Radial Tires with Silver Spoke Wheels
- Smooth Jeep Fenders (Smooth Teardrop Fenders on 7' Wide Models)
- White .024 Aluminum Exterior (With Screws)
- 1-Piece Aluminum Roof
- 12v LED Exterior Lighting (New LazerMax™ exclusive clearance light)
- 12v LED Slim Line Tail Lights
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist (Single Swing Door on 5'W Models)
- 16" Ramp Extension
- 32" Side Entry Door with Bar Lock (No Side Door on 5'W Models)
- 12v Dome Light with Self-Switch
- 3/4" High Performance PlexCore™ Decking
- Economy Sidewall Liner
- 500 lb. Wall Mounted Rope Rings (4)
- Spring Axles with 4" Drop
- E-Z Lube® Hubs
- Undercoated Chassis
- 16" OC Vertical Posts
- 16" OC Crossmembers
- 24" OC Tube Roof Bows
- 1-Year Limited Warranty

## **DELUXE PACKAGE UPGRADES**

- .030 Aluminum Exterior
- Exterior Color Options
- ATP Nose Trim
- 3/8" High Performance PlexCore<sup>TM</sup> Sidewall Liner
- [4] 5,000 lb. Floor D-Rings (500 lb. Wall Rope Rings on 5'W models)



Model FT716T2



Deluxe interior shown with 3/8" PlexCore Sidewall Liner & 5,000 lb. Floor D-Rings.

