



SPEC	IFICATIONS	REVV8524T3
Body:	Length	26'0"
	Width	8'4"
Overall:	Length	29'0"
	Width	8'6"
	Height	9'2"
Interior:	Length	25'6"
	Width	8'1"
	Height	7'0"
Width Between Wheel Boxes:		83"
Platform Height:		18"
Axle:	Quantity	Tandem
	GVWR	9,990 lbs.
	Suspension	Spring
	Electric Brakes	Standard
Tires:	Size	ST225/75R15
	Load Range	D
	Туре	Radial
Hitch:	Ball Size	2 5/16"
	To Top of Ball	21"
Rear Door:	Style	Ramp
	Beavertail Length	48"
	Width x Height	94" x 80"
	Hardware	Bar Locks
Flush Lock Side Door:		48" x 78"
Tube Main Rails		2" × 6"
Curb Weight		4,480 lbs
Payload Capacity		5,510 lbs.
12V Trailer Connector		7-way

STANDARD FEATURES

- Roof and Sidewall Design -16" OC Floor Crossmembers -16" OC Wall Posts

 - -16" OC Roof Framing
- 12" Extended A-Frame with Center Tube
- Smooth .030 Bonded Aluminum Exterior
- Sidewall Flow-Thru Vents
- Polished Aluminum Rear Corners & Rear Header
- 24" Stoneguard
- 48" Side Entry Door with Flush Lock & Recessed Step
- Bar Lock Assembly on Side Door (Add'l Security)
- 9mm White Vinyl Sidewall Liner
- White Vinyl Ceiling Liner
- Black Coin Rubber Floor & Ramp Covering
- Straight Base Cabinet with Black Coin Countertop
- Overhead Cabinet
- 16" ArmorTech Covered Ramp Extension
- 5000 lb. D-Rings (4)
- 15" Radial Tires
- Black SpitFire Aluminum Wheels
- Slim Line LED Tail Lights (Clear Lens)
- 12v LED 14" Ceiling Lights (4)
- 120v 15a Duplex Recepts (2)
- 120v 30A Motorbase with Twist Lock Connect
- 120v 30A Power Cord/Plug 25'
- 30 Amp AC/DC Power Distribution Panel with Converter
- 3 Year Limited Warranty

POPULAR OPTIONS

- Phantom Trim Package
- LED Race Light
- Frame & Wire for Roof Mount A/C



