

The Wells Cargo logo is a black circle with the words "WELLS" and "CARGO" stacked vertically in white, bold, sans-serif capital letters. It is set against a yellow background that is part of a larger graphic element on the left side of the page.

**WELLS  
CARGO®**

# ROAD FORCE® V-FRONT AUTO THE SMART CHOICE

## BEYOND THE STANDARD

Unlike the other models in the Road Force® line-up, the 8.5' wide V-front is an auto hauler at heart. If you're a collector or racer looking for superior quality, durability and style, then the 8.5' wide Road Force® V-front is a smart choice. For starters, the Road Force® features a bonded exterior, an extra wide 94" rear ramp door opening, no-show beavertail, side entry door with recessed step, sidewall vents and tie-down rings - all standard. Factor in the radial tires, LED slim line tail lights, ArmorTech™ Covered A-Frame and a 3-year limited warranty; now you know you've got a trailer that's packed with value and built to last!



Trailers shown may feature optional equipment available at an additional charge.

**ROAD FORCE®**



# SPECIFICATIONS

# ROAD FORCE®



	RFV8516T2	RFV8520T2	RFV8524T2	RFV8528T3
<b>Body:</b> Length	17' 10"	20' 9"	24' 9"	29' 10"
Width	8' 4"	8' 4"	8' 4"	8' 4"
<b>Overall:</b> Length	19' 6"	23' 6"	27' 6"	31' 6"
Width	8' 6"	8' 6"	8' 6"	8' 6"
Height	8' 7"	8' 7"	8' 7"	8' 7"
<b>Interior:</b> Length (Includes "V")	17' 6"	21' 6"	25' 6"	29' 6"
Width	8' 0"	8' 0"	8' 0"	8' 0"
Height	6' 6"	6' 6"	6' 6"	6' 6"
<b>Platform Height</b>	17"	17"	17"	18"
<b>Spring Suspension E-Z Lube® Axles: Qty</b>	Tandem	Tandem	Tandem	Tandem
<b>Total Axle Capacity</b>	7,000 lbs.	7,000 lbs.	7,000 lbs.	10,400 lbs.
<b>Brakes with Breakaway Kit</b>	Electric Drum	Electric Drum	Electric Drum	Electric Drum
<b>Radial Tire Size</b>	ST205/75R15	ST205/75R15	ST205/75R15	ST225/75R15
<b>Tire Load Range</b>	C	C	C	D
<b>Hitch Ball Size</b>	2-5/16"	2-5/16"	2-5/16"	2-5/16"
<b>Hitch Height to Top of Ball</b>	20"	20"	20"	21"
<b>Hitch Weight (% of Curb Weight)</b>	10% to 15%	10% to 15%	10% to 15%	10% to 15%
<b>Curb Weight (Approximate)</b>	2,580 lbs.	3,220 lbs.	3,860 lbs.	4,680 lbs.
<b>GVWR</b>	7,000 lbs.	7,000 lbs.	7,000 lbs.	9,990 lbs.
<b>Payload Capacity (Approximate)</b>	4,420 lbs.	3,780 lbs.	3,140 lbs.	5,310 lbs.
<b>Rear Ramp Door Opening - Width x Height</b>	94" X 72"	94" X 75"	94" X 75"	94" X 75"
<b>12V Male Connection</b>	7-way	7-way	7-way	7-way
<b>Beavertail</b>	Optional	48"	48"	48"

# STANDARD FEATURES

- Exclusive Bull Nose Profile
- Silver Spoke Wheels with 15" Radial Tires
- Smooth Aluminum Fenderettes
- .030 Aluminum Exterior
- .080 Aluminum Top Wrap
- 1-Piece Aluminum Roof
- 12v LED Slim Line Tail Lights
- 12v LED Heavy-Duty Oval Clearance Lights
- 24" ATP Stoneguard
- Flow-Thru Sidewall Vents
- 48" Beavertail — 20'L & Up (*Optional 24" Beavertail on 16'L models*)
- Rear Ramp Door with Spring Assist
- 16" Ramp Extension
- 36" Side Entry Door with Flush Lock
- Recessed Step at Side Door
- 12v LED Dome Light with Wall Switch (2)
- 3/4" PlexCore™ Decking
- 3/8" PlexCore™ Sidewall Liner
- 5,000 lb. Square D-Rings with Welded Plate (4)
- Spring Axles with E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit
- Tube Main Rails
- Entire Chassis Undercoated
- ArmorTech™ on A-Frame and Rear End Rail
- 16" OC Tube Vertical Posts
- 16" OC Crossmembers
- 16" OC Tube Roof Bows
- 3-Year Limited Warranty



*Trailers shown may feature optional equipment available at additional cost.*



[www.wellscargo.com](http://www.wellscargo.com)

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Wells Cargo® dealer for more information.